

DURA DANCE HOME™



**UL GreenGuard Gold
certified underlayment**



10026403

100 sq. ft. (3 ft. x 33.34 ft.)

Add spring to your step with the Dura Dance Home System.

Fitness instructor, fledgling ballerina, or emerging dance troupe – the Dura Dance Home System is in step with any talent or budget level.

Dura Dance can be installed underneath approved floorings and absorbs energy exceptionally well while providing an even and consistent dampening effect. Concrete and other solid surfaces can create bodily injury, but Dura Dance Home helps reduce the chance of injury without missing a beat.

Applications:

Ideal for all types of dance and aerobic exercise, including Zumba, Tap, Hip-Hop and Stress Running. It's also great for dance practice spaces and workplace gyms, just to name a few.

Installation Method (see complete details on back):

Floating floor with quick-click flooring. And because it's "floating" (unsecured to the sub floor), it can be uninstalled easily to restore your room to its original appearance.

Floors to Use:

Quick Click Solid Bamboo (min. 1/2" thickness)

Quick Click Engineered Hardwood (min. 1/2" thickness)

DreamHome Laminate *without* attached pad (min. 12 mm thickness)

**For professional-grade solutions, please call
our ProSales Fitness Department at 888-229-8281.**

**LUMBER
LIQUIDATORS**

IS NOW

LL Flooring™

lumberliquidators.com

PRODUCT SPECIFICATIONS

Add spring to your step with the Dura Dance Home System

ADVANTAGES

- **Dura Dance Home Underlayment™** is made with 100% high-density synthetic foam rubber
- Contains **Ultra-Fresh®**, an antimicrobial protection that resists mold and mildew
- Provides cushioned comfort under wood flooring
- Eliminates minor subfloor imperfections
- Excellent thermal properties

APPROVED SUBSTRATES

- Wood or concrete CLEAN-FLAT-DRY Concrete must be completely cured (at least 30 days old with HVAC operating)
- ¾" interior plywood, OSB flooring, gypcrete
- Waterproofing and crack-isolation membranes
- Cement backer units
- Existing vinyl, wood, and laminate floors

TECHNICAL DATA

100% High-Density synthetic foam rubber.

Thickness.....	3/8"
Density	16 LBS
Weight.....	7.95 oz/sq.ft.
Antimicrobial Treatment	ULTRA-FRESH™
Thermal Resistance.....	R-Value .93
Compression Resistance ASTM D3676.....	9.47 psi
Compression Set ASTM D3574.....	41.1 %
Flammability Rating.....	Passes Federal Flammability Standards DOC-FF-1-70
Product Emissions	Exceeds VOC emissions requirements, environmentally friendly

FLOOR PREPARATION

- Subfloor should be clean and dry
- Follow the wood manufacturer's installation instructions for any additional preparation

QUICK AND EASY INSTALLATION

1. Install **Dura Dance Home Underlayment™** with fabric side up.
2. Use 6 mil moisture vapor film over concrete subfloors. Roll out first roll of underlayment next to the wall. Roll out next row in same manner butting underlayment close to first row (do not overlap). Tape seams with a moisture-resistant tape.
3. Install flooring according to the wood manufacturer's installation instructions.
4. This underlayment can be installed underneath Quick Click Solid Bamboo (1/2" thickness), Quick Click Engineered Hardwood (7/16" thickness) and Laminate floors without attached pad (min 14mm thickness)

PACKAGING

- Available in 3' x 33.34' (100 sq. ft.) rolls



IS NOW

LL Flooring™

6115 Engineered Wood Way
Sandston, Virginia 23150
lumberliquidators.com

MADE IN U.S.A.

